




**Function:**

The **352 Tagelus® Series Sand Filter** consists of a one-piece, fiberglass reinforced tank with UV resistant surface finish for years of unequaled strength and durability. The units are equipped with a six-position, clamp style, top mounted multi-port valve. A combination sand and water drain makes servicing fast and easy.



**Key Features:**

- One-piece fiberglass reinforced tank with UV resistant surface finish.
- 50 psi maximum operating pressure.
- Six position, clamp style, top mounted, multi-port valve.
- 1-1/2" threaded connectors.

**353 Series**

**Side Mount Sand Filter**

**#353-040D Sand Filter:**  
40 GPM design flow rate. 19-1/2" diameter x 37" high; requires service clearance height of 47"; 1.8 sq. ft. of filter area.

**#353-050D Sand Filter:**  
50 GPM design flow rate. 21-1/2" diameter x 39-1/2" high; requires service clearance height of 51-1/2"; 2.3 sq. ft. of filter area.

**#353-060D Sand Filter:**  
60 GPM design flow rate; 24-1/2" diameter x 42-1/2" high; requires service clearance height of 57"; 3.1 sq. ft. of filter area.

**#353-100D Sand Filter:**  
100 GPM design flow rate. 30-1/2" diameter x 47-1/4" high; requires service clearance height of 65-1/2"; 4.9 sq. ft. of filter area.

Model	Order #	Description	Shipping Weight
353-040D	423-42356	Top Mount Sand Filter- 40 GPM	24.0 lbs
353-050D	423-42357	Top Mount Sand Filter- 50 GPM	28.0 lbs
353-060D	423-42358	Top Mount Sand Filter- 60 GPM	30.0 lbs
353-100D	423-42359	Top Mount Sand Filter- 100 GPM	47.0 lbs