



### Function:

The **356 Star® Series D.E. Filter's** patented “swish and bump” system totally dislodges accumulated dirt and diatomaceous earth for periodic cleaning without disassembly. Exclusive, rotatable grid assembly lifts out easily for any required service.

### Key Features:

- Maximum Operating Pressure 50 psi.
- Time-proven vertical grids with 2” spacing provide the most efficient D.E. filtration available.
- Exclusive, rotatable grid assembly lifts out easily for any required service.
- Easy to remove, 1-1/2” drain plug allows rapid draining of filter. Star D.E. filters are available in your choice of 35 gpm, 50 gpm, or 80 gpm capacities.
- Super-strong tanks are molded from advanced, corrosion-proof thermoplastic material.
- Sturdy tank clamp of premium stainless steel allows for quick and easy removal of top for access to grids.
- Unique check valve is built into filter inlet port to prevent backflow of D.E. powder into pump.



## 356 Series

### D.E. Filter

**#356-035 D.E. Filter:** 35 GPM flow rate. 13-3/4” diameter x 29-3/4” high; requires service clearance height of 38”; 7.6 sq. ft. of filter area.

**#356-050 D.E. Filter:** 50 GPM flow rate. 13-3/4” diameter x 37-3/8” high; requires service clearance height of 50”; 11.4 sq. ft. of filter area.

**#356-080 D.E. Filter:** 80 GPM flow rate; 13-3/4” diameter x 44” high; requires service clearance height of 63”; 15.2 sq. ft. of filter area.

Model	Order #	Description	Shipping Weight
356-035	430-43009	D.E. Filter- 35 GPM	24 lbs
356-050	430-43010	D.E. Filter- 50 GPM	44 lbs
356-080	430-43011	D.E. Filter- 80 GPM	48 lbs