



Function:

The **351 Series Stainless Steel Cartridge Filter** features an upflow design that makes the unit one of the safest in the world. Air cannot be trapped inside during operation. There is no need for tricky manual air relief during start-up, no need to make provisions for backwash disposal, no moving parts, no complicated valves...just simple, efficient, safe, quality filtration.



351 Series

Cartridge Filter

#351-055 Cartridge Filter:
55 GPM; approximate height of 19-1/2"; requires a service clearance height of 30"; 55 sq. ft. of filter area.

#351-075 Cartridge Filter:
75 GPM; approximate height of 25"; requires a service clearance height of 45"; 75 sq. ft. of filter area.

#351-105 Cartridge Filter:
105 GPM; approximate height of 29-1/2"; requires a service clearance height of 49"; 105 sq. ft. of filter area.

#351-155 Cartridge Filter:
155 GPM; approximate height of 39-1/2"; requires a service clearance height of 69"; 155 sq. ft. of filter area.

Key Features:

- Type 304 stainless steel construction.
- Automatic, internal air relief.
- 12" diameter footprint area.
- 2" N.P.T. bottom inlet and outlet connections.

Model	Order #	Description	Shipping Weight
351-055	400-40000	Stainless Steel Cartridge Filter- 55 GPM	27.0 lbs
010-ST 55	400-40009	Cartridge for 55 GPM Cartridge Filter	1.5 lbs
351-075	400-40001	Stainless Steel Cartridge Filter- 75 GPM	31.0 lbs
010-0689-75	400-40010	Cartridge for 75 GPM Cartridge Filter	1.5 lbs
351-105	400-40002	Stainless Steel Cartridge Filter- 105 GPM	39.0 lbs
010-ST 105	400-40011	Cartridge for 105 GPM Cartridge Filter	2.0 lbs
351-155	400-40003	Stainless Steel Cartridge Filter- 155 GPM	50.0 lbs
010-ST155	400-40012	Cartridge for 155 Cartridge Filter	2.0 lbs

Toll Free: 887.426.4622
 Phone: 770.457.3000
 Fax: 770.457.4225
www.hobbsfountains.com