



Function:

The **354 Sand Dollar® Series Sand Filter** consists of a one-piece filter featuring a clamp style, six-position multiport valve. Special lateral design provides superior flow characteristics and long filter cycles for economical operation.



Key Features:

- Six position, top mounted multiport valve
- Combination water and sand drain makes servicing and winterizing fast and easy

354 Series

Top Mount Sand Filter

#354-315 Sand Filter: 35 GPM design flow rate. 16-1/2" diameter x 28-1/2" high; requires service clearance height of 33-3/4"; 1.4 sq. ft. of filter area.

#354-320 Sand Filter: 40 GPM design flow rate. 19-1/2" diameter x 34" high; requires service clearance height of 42-7/8"; 1.8 sq. ft. of filter area.

#354-322 Sand Filter: 60 GPM design flow rate; 22-1/2" diameter x 35-1/2" high; requires service clearance height of 47-1/2"; 2.3 sq. ft. of filter area.

#354-333 Sand Filter: 75 GPM design flow rate. 26" diameter x 45-1/2" high; requires service clearance height of 71"; 3.5 sq. ft. of filter area.

Model	Order #	Description	Shipping Weight
354-315	423-42361	Top Mount Sand Filter- 35 GPM	22.0 lbs
354-320	423-42362	Top Mount Sand Filter- 40 GPM	24.0 lbs
354-322	423-42363	Top Mount Sand Filter- 60 GPM	28.0 lbs
354-333	423-42364	Top Mount Sand Filter- 75 GPM	76.0 lbs